

Combi Antenna/Gas Weathering Tile CAG

Application

The CAG Weathering Tile from J.A. Plast is developed especially for leading outlets from gas installations etc. safely through the roof surface. The matching top changes the Weathering Tile into an Antenna Weathering Tile.

Please refer to national standards.

- For pitched roofs
- For gas outlets Ø 114 mm
- For antenna Ø 30-40-60 mm
- Can be manufactured for any profile

Design

CAG is supplied in 3 parts. Installed on a base plate the bottom part is shaped to fit the roof profile 100%. The middle part for pipe Ø114 mm is adjustable to follow the pitched roof from 15° to 45° and is designed to lead the gas outlet safely through the roof surface. With the matching top it can also be used for antenna. The Weathering Tile is supplied with fixings for assembling and is easily installed with the rest of the roofing material.

Colour and Surface

Special coloured, glossy or structured with sand of granules the vents can be supplied with a 100% colour and surface match individually adjusted to each roofing material.

Materials

The weathering tile is manufactured from HIPS (High Impact Polystyrene).

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.



Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.