

Tube Tile TT

Application

Tube Tile from J.A. Plast is developed specially for leading pipes safely through the roof surface e.g. from solar systems.

Please refer to national standards.

- For pitched roofs 15° – 45°
- Can be manufactured for any profile

Design

Available as:

TT-1 – with rubber sleeve, water stop and 2 drain holes. Max. Ø 46 mm pipe. For slates, steel and corrugated sheets.

TT-2 – with rubber sleeve
Max. Ø 46 mm pipe. For clay and concrete.

TT-3 – with water stop and 2 drain holes.
Max. Ø 90 mm pipe. For slates, steel and corrugated sheets.

TT-4 – cast in one piece.
Max. Ø 90 mm pipe. For clay and concrete.

TT-5 – with rubber sleeves, water stop and 2 drain holes. 2 pipes max. Ø 27 mm.
For slates, steel and corrugated sheets.

TT-6 – with rubber sleeves.
2 pipes max. Ø 27 mm. For clay and concrete.

The tube tile is supplied installed on a base plate shaped to match the roof profile 100%. Easily installed with the rest of the roof and discreetly integrated in the roof surface.

Colour and Surface

Special coloured, glossy or structured with sand of granules the vents can be supplied with a 100% colour and surface match individually adjusted to each roofing material.

Materials

Tube Tile is manufactured from HIPS (High Impact Polystyrene).

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.



Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.