

Felt Penetration Sleeve UV2000

Application

The UV2000 from J.A. Plast is for safe penetration of the roof underlay, for ventilation of the batten cavity or for leading through pipes. It is suitable for all standard flexible membranes.

Please refer to national standards.

- Ø 98 mm = 7,500 mm² ventilation area
- Quick and easy installation
- Insect inhibitor
- For flexible membranes

Design

The UV2000 is specially designed for installation in flexible membranes. The seal ring forces the surrounding membrane upwards, diverting water safely away from the opening.

The mesh cover protects against snow and insects. The UV2000 is quick and easy to install with a Stanley knife as only tool required. The felt penetration sleeve is supplied in bags of 10, with fixing instructions and template for cutting membrane.

Colour

The felt penetration sleeve is supplied in transparent white.

Materials

The felt penetration sleeve is manufactured from Polyethylene.

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.

For more detailed installation guide see separate data sheet No. 5.11-04.2009.



Seal ring installed.



The mesh cover in place.

Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.