

# Felt Penetration Sleeve UV2003

## Application

The UV2000 from J.A. Plast is for safe penetration of the sarking for ventilation of the batten cavity. It is suitable for all standard boarded under roofs.

*Please refer to national standards.*

- Ø 105 mm = 5,200 mm<sup>2</sup> ventilation area
- **Quick and easy installation**
- **Insect inhibitor**
- **For boarded roofs**

## Design

UV2003 is specially designed for installation in boarded under roof. The edge around the mesh diverts water safely away from the opening. The integrated mesh protects against snow and insects.

The UV2003 is quick and easy to install. Cut a Ø 110mm hole. Fasten and seal with suitable sealant.

## Colour

Standard colour is black, but all colours are possible depending on quantity.

## Materials

The felt penetration sleeve is manufactured from Polyethylene.

## Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.

For more detailed installation guide see separate data sheet No. 5.15-04.2009.



*Drill a Ø 110 mm hole.*



*Apply suitable sealant on the UV2003 and fix to the board.*



*Quick and safe installation.*

*Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, [www.japlast.com](http://www.japlast.com).*