

Sanitary Vent HV110

Application

The HV110 vent from J.A. Plast is primarily a sanitary vent. It is ideal as ventilation outlet from living quarters like kitchen, bathroom and laundry room or as stack pipe. HV110 can also be used for mechanical ventilation.

Please refer to national standards.

Available as:

HV110 ISO – with insulated pipe
Ø 110 mm pipe fixed from factory

HV110 Solo – with non-insulated pipe
Ø 110 mm pipe fixed from factory

- For pitched roofs 15° – 45°
- 9,000 mm² ventilation area
- Can be manufactured for any profile

Design

The design of the HV110 vent diverts water around the vent and down the roof surface. It has a built in protective grille to keep out leaf fall. The vent is supplied installed on a base plate shaped to fit the roof profile 100%. Easily installed with the rest of the roofing material and always following the roof pitch, the vent presents a nicely integrated solution.

Colour and Surface

Special coloured, glossy or structured with sand or granules the vents can be supplied with a 100% colour and surface match individually adjusted to each roofing material.

Materials

Vent and adapter are manufactured from HIPS (High Impact Polystyrene).

The Tubivent is manufactured from PP (PolyPropylene).

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.



Accessories



Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.