

Sanitary Vent LV200

Application

The cowl vent LV200 from J.A. Plast is a discreet ventilation solution and ideal for outlet of air from living quarters like kitchen, bathroom, tumbler, laundry room and as stack pipe.

LV200 can also be used for mechanical ventilation.

Please refer to national standards.

- For pitched roofs 15° 45°
- 20,000 mm² ventilation area
- · Can be manufactured for any profile

Design

The LV200 vent is designed especially for humid climates where requirements for ventilation are even more essential. Rain is diverted around the vent and a built in protective grille keeps out insects and drifting snow. The vent is supplied installed on a base plate shaped to fit the roof profile 100%. Easily installed with the rest of the roofing material and always following the roof pitch, the vent presents a nicely integrated solution.

The Ø 160mm adapter allows for connection of Multiadapter and Tubivent.

Colour and Surface

Special coloured, glossy or structured with sand or granules the vents can be supplied with a 100% colour and surface match individually adjusted to each roofing material.

Materials

Vent and adapters are manufactured from HIPS (High Impact Polystyrene).

The Tubivent is manufactured from PE (PolyEthylen).

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.





Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.